

H₂OFF

SPRAY FOR PROFESSIONAL USE



H2OFF ELECTRIC

E101050 - 150ml

E10050 - 50ml

TE1000 - 1L

TE5000 - 5L



- Protects electrical and electronic equipment from all types of moisture: steam, condensation, salt, fog, rain, acid rain, salt water and chlorinated water
- Protects against corrosion
- Protects against static electricity and reduces the risk of short circuit
- Protect from frost the electrical and electronic contacts
- Prevents oxidation, the formation of vegetation and mildew on the electrical contacts
- Improves electrical insulation and quality of the contacts, prevents electrical leakage
- Restores the functionality of electrical contacts, electrical and electronic devices that have been exposed to water, moisture, oxidation, corrosion
- Cleans and protects from dust and dirt from the electrical contacts
- Extends the life of electrical and electronic appliances in extreme weather conditions

INDICATIONS FOR USE:

- SWITCHBOARDS, ELECTRICAL BOXES
- INDUSTRIAL EQUIPMENT , PETROCHEMICAL PLANTS
- CONSTRUCTION MACHINERY, WELDING EQUIPMENT
- AGRICULTURAL EQUIPMENT
- LIGHTING FOR OUTDOOR, LIGHT BOX, OUTDOOR ADVERTISING PROJECTORS
- ELECTRIC MOTORS , ELECTRICAL EQUIPMENT OF ALL KINDS, DRILLS, LATHES, SAWS, MOWERS
- ACCESSORIES FOR ELECTRICAL EQUIPMENT: GENERATORS, POWER STRIPS, TERMINALS, SOCKETS, TRANSFORMERS, GEARS
- SECURITY AND OBSERVATION SYSTEMS: ALARMS, SECURITY SENSORS AND MONITORING SYSTEMS
- VIDEO SURVEILLANCE CAMERAS AND MICROPHONES.
- COMPONENTS OF COMPUTER, MOTHERBOARDS, MEMORY BOARDS, INPUT DEVICES, ETC..
- FUSE BOXES, FANS, GENERATORS, STARTER, WINDSHIELD WIPERS, ELECTRIC LOCKS, HEATERS, ELECTRIC WINDOWS, COOLING SYSTEMS

H2OFF ANTICORROSION

A10150 - 150ml

A10050 - 50ml

TA1000 - 1L

TA5000 - 5L



H2OFF sealant allows to seal crack and slots on different types of material. Thanks to an elastic film resistant to temperature change, adheres firmly to the surface making it fully waterproof.

- Adheres to any surface (concrete, bricks, plastic, metal, paper, PVC, wood)
- After the application, in about one hour form a durable protective film.
- Resistant to temperature changes
- It prevents moisture penetrating into the treated surface.
- Resistant to extreme situations: rain, wind, sea water, etc.
- It is not soluble in water.

INDICATIONS FOR USE:

- PROTECTION OF ELECTRICAL WIRES FROM WEATHER;
- SEAL JUNCTION BOXES, the sealant resists also if the box is buried in the ground.
- PROTECTION OF BOXES OF EXTERNAL CONNECTORS AND ELECTRIC GATES FROM INFILTRATION WATER AND PARASITES.
- FOR PERMANENT REPAIR OF CRACKS AND SLOTS IN THE WALLS, DRAPES, WOOD, PVC THAT HAVE BEEN DRILLED OR CRACKED
- WATERPROOF THE SURFACE TREATED
- TO FIX, SATELLITE TELEVISION OR SOLAR PANELS.
- PROTECTS AGAINST CORROSION

H2OFF RAILWAY ELECTRIC

RE0150 - 150ml
RE1000 - 1L
RE5000 - 5L



- Can be applied on wet surfaces
- Thanks to its high capillary capacity fills micro cavity and micro cracks reaching the deepest parts of equipments, without the need to disassembling them
- Retains conductivity of components in water
- Forms an insulation coating that prevents surface leakage current
- Does not damage metals, plastic, rubber, glass, paint, ceramics and electric motors
- Penetrates beneath the oxide, which is easier to remove and prevents its formation
- It allows a considerable maintenance saving

INDICATIONS FOR USE:

- ON VEAM CONNECTORS
- ON FRONT-PLATES AND REAR-PLATES OF TERMINAL BOXES
- ON RAILWAY SWITCH BALDE CONTACTS AND CONTROL CONTACTS OF LAND DEVICES
- ON LAMP HOLDERS OF TURNOUTS DISKETTES AND ALL LIGHT SIGNALS
- ON ALL INTERNAL ELECTRICAL CONNECTIONS OF LOCKING DEVICES OF RAILWAY SWITCHES
- ON ALL CONTACTS OF POWER SUPPLIES, SCREEN RELAYS, HEADLIGHTS
- ON ALL CONTACTS OF TRANSFORMERS, BRIDGES, RESISTORS AND DISCHARGERS OF TRACK CIRCUIT
- ON ALL CONTACTS TO RAIL AR60, AR67, CABLE TERMINALS AND LUGS
- ON ALL CONTACTS OF PEDALS' PLATES
- ON AMP AND BURNDY CONNECTORS, ON SHORT, MEDIUM AND LONG SPINNING MILLS AND LAND TERMINAL CONTACTS
- ON CONNECTORS BETWEEN DIFFERENT WAGONS, ON ALL END SWITCHES AND ROLLING STOCK SAFETY CONTACTS
- ON ELECTRICAL EQUIPMENT POSITIONED NEAR THE TRACK SUBJECT TO DIRT AND MOISTURE
- ON TRAIN LIGHTS AND ON ALL LAMP HOLDERS
- ON ELECTRICAL EQUIPMENT, RELAYS, CONNECTORS, FRONT-PLATES AND BACKPLATES
- ON BUSHINGS TEMPERATURES DETECTION SENSORS
- LAMPS AND CONTACTS LOCATED IN ENVIRONMENTALLY DIFFICULT PLACES SUCH AS UNDERPASSES AND INSPECTION PITS
- IN PLACES WITH HIGHER FIRE RISK AND SUBJECT TO THE ATEX NORMS AS A GUARANTEE OF THE SUPPLEMENTARY PROTECTION THAN STANDARD PRECAUTIONS

H2OFF RAILWAY ANTICORROSION

RL0150 - 150ml
RL1000 - 1L
RL5000 - 5L



- Protects metal components and systems from all forms of humidity: vapor, condensed moisture, splashes, fog, acid rain, chlorinate water, salt water
- Restores the operation of devices already damaged by exposure to humidity
- Considerably extends systems and equipment working life
- Has an excellent lubricant effect wich after application don't attract dust
- Protects against H2S corrosion
- Prevents corrosion and stops corrosion already in progress
- Can be applied on wet surfaces and does not require pre-treatment
- Forms waterproof and water repellent coating (fills micro cavity and micro cracks and expels accumulated water and dirt)
- Penetrates under rust, facilitates rust removal, forms protective coating
- Retains elasticity of rubber parts like seals and gaskets, eliminates efficiently squeaks and mechanical friction
- Does not damage metals, plastic, rubber, glass, varnish, paint, ceramics and e-lectric motors

INDICATIONS FOR USE :

- ON MANEUVER LINKAGES OF RAILWAY SWITCHES
- ON THE OF SHOCK PREVENTION DEVICES OF RAILWAY SWITCH ELECTROMAGNET PIN OF AND ITS LINKAGE
- IN ALL GEARS AND LEVERS AVOIDING FRICTION AND CENTRIFUGAL CLUTCHES IN RAILCROSSING BOXES.
- ON ROTATION MECHANISM OF TURNOUT DISKS AND DIVERTERS
- ON ALL PARTS WICH ARE SUBJECTED TO WEAR, DIRT AND CORROSION
- ON MECHANISMS OF THE KEY SWITCH LOCKS
- ON SILEC CAUTOR AND FORFEX LEVERS
- ON KNEELING SYSTEMS OF RETRACTABLE FOOTBOARD
- FOR RUBBER PARTS AND SEALS
- ON GEAR TURNOUTS
- ON P40 AND P70 PISTONS AND GEARS
- ON PANTOGRAPH MECHANISM
- ON MET MECHANISM
- ON ALL MECHANICAL PARTS, LEVERS AND GEARS OF ROLLING STOCK

H2OFF SEALANT

TOTAL WHITE

SB0500 - 500ml



H2OFF sealant allows to seal cracks and slots on different types of material. Thanks to an elastic film resistant to temperature change, adheres firmly to the surface making it fully waterproof.

- Adheres to any surface (concrete, bricks, plastic, metal, paper, PVC, wood)
- After the application, in about one hour forms a durable protective film.
- Resistant to temperature changes
- Can be painted
- Prevents moisture penetration by penetrating the treated surface.
- Resistant to extreme situations: rain, wind, sea water, etc.
- It is not soluble in water.

INDICATIONS FOR USE:

- PROTECTION OF ELECTRICAL WIRES FROM WEATHER;
- SEAL JUNCTION BOXES;
- INSULATION;
- WATERPROOF SURFACE TREATED
- PROTECTION OF BOXES OF EXTERNAL CONNECTORS AND ELECTRIC GATES FROM INFILTRATION WATER AND PARASITES.
- FOR PERMANENT REPAIR OF CRACKS IN THE WALLS, DRAPES, WOOD, PVC THAT HAVE BEEN DRILLED OR CRACKED

H2OFF SEALANT

TOTAL BLACK

SN0500 - 500ml



H2OFF sealant allows to seal crack and slots on different types of material. Thanks to an elastic film resistant to temperature change, adheres firmly to the surface making it fully waterproof.

- Adheres to any surface (concrete, bricks, plastic, metal, paper, PVC, wood)
- After the application, in about one hour form a durable protective film.
- Resistant to temperature changes
- It prevents moisture penetrating into the treated surface.
- Resistant to extreme situations: rain, wind, sea water, etc.
- It is not soluble in water.

INDICATIONS FOR USE:

- PROTECTION OF ELECTRICAL WIRES FROM WEATHER;
- SEAL JUNCTION BOXES, the sealant resists also if the box is buried in the ground.
- PROTECTION OF BOXES OF EXTERNAL CONNECTORS AND ELECTRIC GATES FROM INFILTRATION WATER AND PARASITES.
- FOR PERMANENT REPAIR OF CRACKS AND SLOTS IN THE WALLS, DRAPES, WOOD, PVC THAT HAVE BEEN DRILLED OR CRACKED
- WATERPROOF THE SURFACE TREATED
- TO FIX, SATELLITE TELEVISION OR SOLAR PANELS.
- PROTECTS AGAINST CORROSION



NanoProtech Italia srl

Centro Direzionale Milanofiori
Strada 6 Palazzo N/3 20089
Rozzano (MI)
Italy

TEL: +39.0280887194

FAX: +39.02871823031
e-mail: info@h2off.it

